

(51) Internationale Patentklassifikation⁷:

D01G 27/00, B65H 67/06

A1

(11) Internationale Veröffentlichungsnummer: WO 00/28118

(43) Internationales
Veröffentlichungsdatum:

18. Mai 2000 (18.05.00)

(21) Internationales Aktenzeichen: PCT/CH99/00512

(22) Internationales Anmeldedatum: 2. November 1999 (02.11.99)

(30) Prioritätsdaten:

198 51 898.6

11. November 1998 (11.11.98) DE

(71) Anmelder (für alle Bestimmungsstaaten ausser US): MASCHINENFABRIK RIETER AG [CH/CH]; Klosterstrasse 20, CH-8406 Winterthur (CH).

(72) Erfinder; und

(75) Erfinder/Anmelder (nur für US): SCHEURER, Paul [CH/CH]; Holzlegistrasse 8, CH-8408 Winterthur (CH).

(81) Bestimmungsstaaten: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO Patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), eurasisches Patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), europäisches Patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI Patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Veröffentlicht

Mit internationalem Recherchenbericht.

Vor Ablauf der für Änderungen der Ansprüche zugelassenen Frist; Veröffentlichung wird wiederholt falls Änderungen eintreffen.

(54) Title: ROTATING STATION FOR REELS

(54) Bezeichnung: DREHSTATION FÜR WICKEL

(57) Abstract

The invention relates to a method for changing the winding-off direction of reels (W,W1) which are delivered in succession by a delivery station (1) in order to form a reel group (WG) in which the front faces of adjacent reels (W) are equally spaced (a) and the longitudinal axes (LA) of the reels (W) are in a line. In practise, it is sometimes necessary to arrange the preparation machine for producing a reel (W) in such a way in relation to the combing machine group being used that the reels that are delivered by the preparation machine have a different winding-off direction in the ejected winding-off direction to that necessary for the subsequent combing machine. It is therefore necessary to rotate the reels (e.g., 90° or 180°) whilst preserving the division of the reel group. To this end, the reels (W) that are delivered by the delivery station (1) (W) are gradually shifted crosswise to their direction of delivery by a receiving element (41, 42) of a rotating device (30), by which means they come to lie in a plane in which the longitudinal axis (LA) of the reel (W) lies, are rotated and can then be moved out of the area of the receiving element (42) in the direction of its longitudinal axis (LA).

